

# Menard County Fair

## 6500 Pound Modified 4x4 Truck Rules (Class Q1-1-8) Non Sanctioned

1. Hitch height cannot exceed 26 inches.
2. Pull from reese type, bumper, or drawbar type hitch, with no part of hitch in front of the center of the rear axle and nothing above the top of the frame rail. Hooking point must be no less than 42" from center of the rear axle. It must be accessible and RIGID. No floating hitches. Supports from rear axle must be attached to frame only, not the hitch.
3. Under hood inspections can be done at any time.
4. DOT approved tires, 35" max height, no cut or sharpened tires.
5. 540 C.I. limit on block with after market cast block O.K. If you have not been certified to 540 C.I. or less and place in the money, your truck will be checked by the pull officials. Not obeying this rule will result in forfeiture of your winnings.
6. No aluminum heads - cast iron only. Aluminum intake and headers are allowed. No side exit exhaust, and no exhaust should exit out of the hood.
7. Pump fuel only - no alcohol, nitrous, or methane based fuels allowed.
8. OEM stock 1 ton or less drive and OEM brakes.
9. 140" wheelbase or less may have front weights 60" or less from center of front axle. Trucks more than 140" wheelbase cannot have any weights more than 2' from stock bumper location in the front of the truck.
10. Safety chains and loops around are required around drive shafts.
11. All trucks must have driveshaft shield around the rear U-joint and front shaft/front U-joint. It must be 4" from center of U-joint both ways, made from 1/8" thick steel and can be bolted together by 3/8" bolts. Shield can be maximum 4" larger than the diameter of the driveshaft.
12. Scatter blanket or blow proof bell housings and kills switches are mandatory. No dual wheels are allowed.
13. NO WHINING/ARGUING - Judges decisions are final and take precedence over printed material.